

OPTICAL AND IMAGING SYSTEM

1 Top View Camera	XGA 3CCD color camera (1024 x 768)
4 Angled View Cameras	XGA mono camera (1024 x 768)
Lighting	Multi-segment, multi-angle LED, RGB+W
Optical Resolution	10, 15, 20, 25µm
Imaging Method	High-speed dynamic imaging

IMAGING/INSPECTION SPEED

25µm	110 cm <sup>2</sup> /sec
20µm	72 cm <sup>2</sup> /sec
15µm	40 cm <sup>2</sup> /sec
10µm	18 cm <sup>2</sup> /sec

PRE-/POST-REFLOW INSPECTION

Component Defects	Missing, tombstone, billboard, polarity and shift
Solder Joint Defects	Insufficient/excess solder and bridge

X-Y TABLE AND CONTROL

High Precision Ball Screw/Servo Motor with DSP-based motion controller	
X, Y Axis Resolution	1µm

PCB AND DIMENSION

Max. PCB Size	TR7500	510 x 460mm
	TR7500L	660 x 610mm
Max. PCB Thickness	4mm	
PCB Carrier/Fixing	Motor driven/clamping	
Clearance	Top	50mm
	Bottom	50mm
	Edge	3.5mm
Weight	TR7500	850kg
	TR7500L	985kg
Dimensions	TR7500	(W) 1220mm x (D) 1480mm x (H) 2085mm
	TR7500L	(W) 1370mm x (D) 1570mm x (H) 2111mm
Power Supply	200-240V Single phase, 50/60Hz 3KVA	
Optional Solutions	OCR, OCV, coaxial lighting, barcode system, off-line editor, repair station, SPC software and yield management system (YMS)	



Specifications are subject to change without notice. All trademarks are the property of their owners.

The following are trademarks or registered trademarks of Test Research, Inc. (TRI)



The absence of a product or service name or logo from this list does not constitute a waiver of TRI's trademark or other intellectual property rights concerning that name or logo. All other trademarks and trade names are the property of their owners.

Test Research, Inc.

**Headquarters**  
7F., No.45, Dexing West Rd.,  
Shilin Dist., Taipei City 11158, Taiwan  
TEL: +886-2-2832-8918  
FAX: +886-2-2831-0567  
E-Mail: sales@tri.com.tw  
http://www.tri.com.tw

**Hsinchu, Taiwan**  
7F., No.47, Guangming 6th Rd., Zhubei  
City, Hsinchu County 30268, Taiwan  
TEL: +886-3-553-9796  
FAX: +886-3-553-9786

**USA**  
1923 Hartog Drive  
San Jose, CA 95131 U.S.A.  
TEL: +1-408-567-9898  
FAX: +1-408-567-9288  
E-mail: triusa@tri.com.tw

**Malaysia**  
C11-1, Ground Floor, Lorong  
Bayan Indah 3 Bay Avenue,  
11900 Bayan Lepas Penang,  
Malaysia  
TEL: +604-6461171  
E-mail: trimy@tri.com.tw

**Europe**  
O'Brien Strasse 14  
91126 Schwabach  
Germany  
TEL: +49-9122-631-2127  
FAX: +49-9122-631-2147  
E-mail: trieuropa@tri.com.tw

**Japan**  
2-9-9 Midori, Sumida-ku,  
Tokyo, 130-0021 Japan  
TEL: +81-3- 6273-0518  
FAX: +81-3- 6273-0519  
E-mail: trijp@tri.com.tw

**Korea**  
No.207 Daewoo-Technopia,  
768-1 Wonsi-Dong, Danwon-Gu,  
Ansan City, Gyeonggi-Do, Korea  
TEL: +82-31-470-8858  
FAX: +82-31-470-8859  
E-mail: trikr@tri.com.tw

**Shenzhen, China**  
5F3, Guangxia Road, Shang-me-  
lin Area, Fu-Tian District, Shenzhen,  
Guangdong, 518049, China  
TEL: +86-755-83112668  
FAX: +86-755-83108177  
E-mail: shenzhen@cn.tri.com.tw

**Suzhou, China**  
63 Huoju Road, Suzhou New  
District, 215009, China  
TEL: +86-512-68250001  
FAX: +86-512-68096639  
E-mail: suzhou@cn.tri.com.tw

**Shanghai, China**  
W. 6F., Building 18, 481 Guiping  
Road, Shanghai, 200233, China  
TEL: +86-21-54270101  
FAX: +86-21-64957923  
E-mail: shanghai@cn.tri.com.tw

T R 7 5 0 0 A O I



- ULTRA-HIGH-SPEED IN-LINE AOI SYSTEM
- TOP-VIEW DIGITAL 3CCD FULL COLOR CAMERA + 4 ANGLED CAMERAS FOR THE MOST COMPLETE AOI COVERAGE
- RGB+W MULTI-ANGLE LIGHTING CONTROL
- 01005 COMPONENT/12 MIL FINE-PITCH READY
- DESIGNED FOR LEAD-FREE AND LEGACY PCB ASSEMBLIES
- PRE-/POST-REFLOW COLOR AOI OPTIMAL SOLUTION



# A NEW AOI SYSTEM FOR A NEW GENERATION OF SMT



## BEST THROUGHPUT FOR INLINE PRODUCTION

Dynamic imaging technology provides vibration-free imaging of a PCB with high throughput. Inspection speed can be reduced to as little as 14 seconds for a medium-sized board (@25µm, excluding locating fiducial marks and loading time). It is also safe for pre-reflow inspection.

## HIGH RESOLUTION IMAGING SYSTEM

The new 3CCD multiple color and monochrome camera system (top and angled views) and range optical resolutions (10, 15, 20, and 25µm) enable the TR7500 to capture up to 250 frames/sec of standard XGA format images (1024 x 768 pixels). Four angled cameras provide high accuracy for solder joint and lifted lead inspection. With an ultra-high resolution of 10µm, small components such as 01005 chips can be easily inspected.

## MODULARIZED CONTROL SYSTEM


The precision X-Y table, conveyor system, image acquisition, lighting system and the host PC are all independent modules to allow for easy diagnostics and system maintenance.

## ADVANCED COLOR LIGHTING


The new RGB+W lighting control and the color imaging system instantly provide operators with easier visual verification of real images. The advanced color lighting system significantly improves 3D solder fillet reconstruction, providing more accurate inspection results for solder fillet on small components such as 01005 and fine pitch leads.

## EASY PROGRAMMING ENVIRONMENT


- Programming is easily accomplished by using the data from a CAD file directly. The only mandatory data fields are component name, package type, X-position, Y-position, and rotation angle.
- PCBs with special layouts also can be easily edited.
- TRI provides a standard model library for most of the main component types and they are presented graphically for ease of use. This can greatly reduce the time spent creating inspection boxes and setting parameters.
- Accurate warp compensation and a multi-fiducial finding algorithm ensure the correct positioning of the inspection windows, leading to accurate, repeatable defect detection.



Built-in Model Library Function








Color board view for better image clarity



Graphical lighting control editor

Top View (color)


Angle View (mono)



## YIELD MANAGEMENT SYSTEM \*

- Testers enable process capability control
- Real time defect information integration and analysis
- Defect knowledge management

\* Optional



Open