

TR7700 SIII DT SERIES



- High Performance Desktop AOI
- Fast Dynamic Imaging up to 120 cm²/sec
- Smart Programming with IPC standard compliance

DESKTOP AUTOMATED
OPTICAL INSPECTION

TR7700 SIII DT FEATURES


Premium Desktop AOI with World Class Performance

TR7700 SIII DT captures high precision full PCB panel images in unprecedented detail using TRI's exclusive multi-phase lighting. Next generation inspection software combines excellent defect detection and easy programming into a state-of-the-art desktop AOI solution.

Intelligent Easy Programming Interface


New intelligent programming process significantly reduces programming time using intelligent component library and integrated board warp compensation.

Programming Flowchart




Smart Library + Model Library

Smart Library speeds up programming by automatically allocating inspection windows for IC leads.




New Color Space Algorithms

TRI's new adaptive algorithms use color space processing to increase inspection accuracy, reduce false calls and improve inspection results while reducing time necessary for inspection fine tuning and the number of alternative images required.




Color Differentiation Analysis for Black Resin Parts



High Speed with Multi-phase Lighting

Four individual lighting phases improve inspection of individual defect types using specialized lighting conditions. High speed camera allows inspection at constant speed even with multiple lighting phases.



Flexible multi-board Merging & Speedy Inspection

- Simultaneous access to multiple component information for easy programming.
- Saves multi-fiducial mark scanning time for multi-board programs.

Auto-clamping Conveyor System

Single button PCB loading and unloading reduces operator workload and improves board loading time.

High Speed Ballscrew X-Y Motion Drive

Servo motor with high precision control helps deliver stable and reliable inspection results.

SMT Line Integration

Centralized production line management increases operator productivity and response time. TRI's integrated solution includes the following four components.

- Offline Editor

This application allows for centralized independent adjustment and fine tuning of inspection algorithms on previously scanned images while providing immediate feedback. The completed program can then be uploaded to the in-line inspection machines to improve inspection stability and accuracy.

Industry 4.0


TRI's solution for Industry 4.0, YMS 4.0, provides a M2M centralized inspection monitoring and remote access fine tuning throughout the SMT line. Built-in support for SPI, AOI, AXI and ICT systems helps track Alarms and SPC data to simplify production quality monitoring. YMS 4.0 is TRI's Industry 4.0 closed loop software to assure your production line Inspection quality and efficiency.



**INCREASE
EFFICIENCY**



**REDUCE
MANPOWER**




**LEANER
PRODUCTION LINE**

The Yield Management System allows operators to aggregate information from individual TRI inspection systems for statistical analysis of production line defect rates, reviewing and fine-tuning inspection results, and identifying component defect trends and emerging production issues.



PRODUCTION ANALYSIS




CENTRALIZED
INSPECTION CENTER



REAL TIME SPC
TREND

Yield Management System



- Inspection results and data integration
- Real time SPC and production yield management
- Quality reports and closed loop tracking
- Support defect component analysis and improvements
- Knowledge Management (KM)
- Productivity and Quality Management

Optical & Imaging System

Top View Camera	4 MP high speed color camera
Lighting	Multi-phase RGB+W LED
Optical Resolution	10 or 15 μm (factory setting)
Imaging Method	Dynamic Imaging

Imaging/Inspection Speed

15 μm	120 cm^2/sec
10 μm	60 cm^2/sec

Pre-/Post-Reflow Inspection Functions

Component	Missing, Tombstoning, Billboarding, Polarity, Rotation, Shift, Wrong Marking (OCV), Defective, Upside Down, Extra Component
Solder Joint	Excess Solder, Insufficient solder, Bridging, Through-hole Pins, Lifted Lead, Golden Finger Scratch/Contamination


X-Y Table & Control

Ballscrew + AC servo with motion controller	
X-Y Axis Resolution	1 μm

PCB Specification

	TR7700 SIII DT	TR7700L SIII DT
Min. PCB Size	50 x 50 mm (1.97 x 1.97 in.)	
Max. PCB Size	330 x 250 mm (13.0 x 9.84 in.)	510 x 460 mm (20.1 x 18.1 in.)
Max. PCB Thickness	3 mm (0.12 in.)	
Max. PCB Weight	3 kg (6.61 lbs)	
PCB Carrier/Fixing	Motor Driven Clamping	
Clearance		
Top	25 mm (0.98 in.) [48 mm (1.89 in.) optional]	25 mm (0.98 in.) [48 mm (1.89 in.) optional]
Bottom	100 mm (3.94 in.)	50 mm (1.97 in.)
Edge	3 mm (0.12 in.)	3 mm (0.12 in.)

Dimensions



Unit: mm (in.)

	TR7700 SIII DT	TR7700L SIII DT
Weight	340 kg (750 lbs)	385 kg (849 lbs)
Power Requirement	200 – 240 V, single phase, 50/60 Hz 3 kVA	

Options

Barcode Scanner, Repair Station, Offline Editor, OCR, Yield Management System (YMS 4.0), YMS Lite, Support Pin, Bottom Metal Case

Specifications are subject to change without notice. Content may not be used as acceptance criteria. All trademarks are the property of their owners.

TRI 德律 TRI INNOVATION

The absence of a product or service name or logo from this list does not constitute a waiver of TRI's trademark or other intellectual property rights concerning that name or logo. All other trademarks and trade names are the property of their owners.



Headquarters

7F., No.45, Dexing West Rd.,
Shilin Dist., Taipei City
11158, Taiwan
TEL: +886-2-2832-8918
FAX: +886-2-2831-0567
E-Mail: sales@tri.com.tw
http://www.tri.com.tw

Linkou, Taiwan

No.256, Huaya 2nd Rd.,
Guishan Dist., Taoyuan
City 33383, Taiwan
TEL: +886-2-2832-8918
FAX: +886-3-328-6579

Hsinchu, Taiwan

7F., No.47, Guangming 6th
Rd., Zhubei City, Hsinchu
County 30268, Taiwan
TEL: +886-2-2832-8918
FAX: +886-3-553-9786

Shenzhen, China

5F.3, Guangxia Rd.,
Shang-mei-lin Area,
Fu-Tian Dist., Shenzhen,
Guangdong, 518049, China
TEL: +86-755-83112668
FAX: +86-755-83108177
E-mail: shenzhen@cn.tri.com.tw

Suzhou, China

B Unit, Building 4, 78 Xinglin St.,
Suzhou Industrial Park,
215123, China
TEL: +86-512-68250001
FAX: +86-512-68096639
E-mail: suzhou@cn.tri.com.tw

Shanghai, China

Room 6C, Building 14,
470 Guiping Rd., Xuhui Dist.,
Shanghai, 200233, China
TEL: +86-21-54270101
FAX: +86-21-64957923
E-mail: shanghai@cn.tri.com.tw

USA

832 Jury Court, Suite 4,
San Jose, CA 95112 U.S.A
TEL: +1-408-567-9898
FAX: +1-408-567-9288
E-mail: triusa@tri.com.tw

Europe

O'Brien Strasse 14
91126 Schwabach
Germany
TEL: +49-9122-631-2127
FAX: +49-9122-631-2147
E-mail: trieurope@tri.com.tw

Japan

2-9-9 Midori, Sumida-ku,
Tokyo, 130-0021 Japan
TEL: +81-3-6273-0518
FAX: +81-3-6273-0519
E-mail: trijp@tri.com.tw

Korea

No.207 Daewoo-Technopia,
768-1 Wonsi-Dong, Danwon-Gu,
Ansan City, Gyeonggi-Do, Korea
TEL: +82-31-470-8858
FAX: +82-31-470-8859
E-mail: trikr@tri.com.tw

Malaysia

C11-1, Ground Floor, Lorong
Bayan Indah 3 Bay Avenue,
11900 Bayan Lepas Penang,
Malaysia
TEL: +604-6461171
E-mail: trimy@tri.com.tw